

PVT LAND COMPANY, LTD.

Regulatory Limits

The following are acceptable following appropriate test results:

Lead Paint Debris; Requires TCLP (Toxicity Characteristic Leaching Procedure) test result for lead must be below 5.0 MCL (Maximum Concentration Limit).

Sand Blast Sand and Soil: Results for TCLP must be faxed for metals and must not exceed MCL levels listed below:

Analyte	Regulatory Level (mg/1)
Arsenic	5.0
Barium	100.0
Cadmium	1.0
Chromium	5.0
Lead	5.0
Mercury	0.2
Selenium	1.0
Silver	5.0

Other Acceptable Non-Hazardous Contaminated Soil:

Non-Toxic Substances Control Act (TSCA) regulated soils
Heavy metal contaminated soils that meet industrial PRGs

Fiberglass and Steel Waste Storage Tanks must be certified clean by a qualified environmental contractor, results must be submitted to PVT prior to disposal.

Asbestos:

Type I Non-friable floor tiles and roofing tile:

Must be inspected by PVT prior to demolition. If the material is deemed to be in "good condition" and is not pulverized during demolition, the material may be disposed of as regular demolition debris. NESHAP rules apply to demolition and disposal.

Type II Friable Asbestos:

Must be handled by certified asbestos contractor for demolition and disposal in PVT's asbestos pit. See PVT's **ASBESTOS POLICIES**.